O.M.B. No 3067-0077 Expires May 31, 1993

## **ELEVATION CERTIFICATE**

FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM ION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMH). · Instructions for completing this form can be found on the following pages. FOR INSURANCE COMPANY USE SECTION A PROPERTY INFORMATION POLICY NUMBER BUILDING OWNER'S NAME Baxter Companies STREET ADDRESS (Including: Apt., Unit, Suite and/or Bidg. Number) OR P.O. ROUTE AND BOX NUMBER COMPANY, NAIC NUMBER 525' Rivershire OTHER DE SCRIPTION (Lot and Block Numbers, etc.) Lot 101, Rivershire, Lincolnshire ZIP CODE STATE 60069 Illinois Lincolnshire SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION Provide the following from the proper FIRM (See instructions): 6. BASE FLOOD ELEVATION (in AO Zohes, use depih) 5. FIRM ZONE 4. DATE OF FIRM INDEX 2. PANEL NUMBER a. SUFFIX 1. COMMUNITY NUMBER 647 6/11/32 A - 3 C 0005 170373 7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): XNGVD '29 Other (describe on track) 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate SECTION C BUILDING ELEVATION INFORMATION ig the Elevation Certificate instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best ribes the subject building's reference level \_\_\_\_\_. 2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of 16510 12 feet NGVD (or other FIRM datum-see Section B, Item 7). (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of \_\_\_\_\_\_ feet NGVD (or other FIRM datum-see Section B, Item 7). (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is \_\_\_\_\_ feet above \_\_\_ or below (check one) the highest grade adjacent to the building. (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is LLL leet above C or below (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? 

Yes 

No 

Unknown 3. Indicate the elevation datum system used in determining the above reference level elevations: XXNGVD '29 C Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.) 4. Elevation reference mark used appears on FIRM: XXIXYes \( \text{No (See Instructions on Page 4)} \) 5. The reference level elevation is based on: XX actual construction aconstruction construction construction (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.) 6. The elevation of the lowest grade immediately adjacent to the building is: 1648.7 leet NGVD (or other FIRM datum-sec Section B, Item 7). SECTION D COMMUNITY INFORMATION

e community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest floor" as defined by the ordinance is: Lilling feet NGVD (or other FIRM datum-see Section B, Item 7).

REPLACES ALL PREVIOUS EDITIONS

2. Date of the start of construction or substantial improvement


## SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1-A30, AE, AH, A (with BFE),V1-V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features-II the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the day available, I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001. 38298

		•	REGISTERED \	1
Paul H. Ulatowski		33298	FROFESSIONAL .	
CERTIFIER'S NAME	LICE	NSE NUMBER (or Affix Seal)	ENGINTER /	¥
<u>Partner</u>	Henderson	and Bodwell	OF OF	7
TITLE	COMPANY NAME			#
124 Hest Diversey	Elmhurst		II MOVIEINOISON 2	6
ADDRESS YELF HELLELLE	· CITY	12/6/91	(708) 834-9406 ··	
SIGNATURE	•	DATE	PHONE .	
Copies should be made of this Certificate for: 1) con	mmunity official, 2) i	nsurance agent/comp	pany, and 3) building owner.	_
COMMENTS:	·	•		
				D
				_



The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.